

Issue Date: 21-Dec-2004

Revision Date: 21-Apr-2022

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Flaw-Finder AG-2D-DH Penetrant Developer

Other means of identification

SDS # AGC-203-1

Product Code AG-2D-DH

UN/ID No UN1950

Other Information Package type: Gallon, 5 Gallon Pail, 55 Gallon Drum

Recommended use of the chemical and restrictions on use

Recommended Use Penetrant Developer.

Details of the supplier of the safety data sheet

Manufacturer Address

AMERICAN GAS & CHEMICAL COMPANY, LTD
 220 Pegasus Avenue
 Northvale NJ 07647

Emergency Telephone Number

Company Phone Number Phone: 201-767-7300 Fax: 201-767-1741

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Milky Liquid

Physical State Liquid

Odor Sweet odor

Classification

Acute toxicity - Inhalation (Dusts/Mists)

Category 4

Skin sensitization

Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

May be harmful in contact with skin

Causes mild skin irritation



Signal Word

Warning

Hazard Statements

Harmful if inhaled

May cause an allergic skin reaction

May cause eye irritation

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a poison center or doctor/physician

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
1,2-Trans-Dichloroethylene	156-60-5	<40
Methyl Nonafluoro-Isobutyl Ether	163702-08-7	<25
Methyl Nonafluoro-Butyl Ether	163702-07-6	<25
Acetone	67-64-1	<7
Talc	14807-96-6	<3
Silicon Dioxide	7631-86-9	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES**First Aid Measures**

Eye Contact	If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call physician.
Skin Contact	Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	Remove to fresh air. Call a physician immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
Ingestion	Do not induce vomiting. Call a physician immediately. Potential for aspiration if swallowed.

Most important symptoms and effects

Symptoms	High vapor concentrations are irritating to the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects. Prolonged or repeated skin contact tends to remove skin oils possibly leading to irritation and dermatitis. Contact may cause eye irritation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.**Specific Hazards Arising from the Chemical**

Pressurized container: May burst if heated.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions	Remove all sources of ignition. Use personal protective equipment as required. Ventilate confined spaces.
Environmental Precautions	Try to prevent the material from entering drains or water courses.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
--------------------------------	---

Methods for Clean-Up Contain and collect with an inert absorbent and place into an appropriate container for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Use personal protection recommended in Section 8. Avoid breathing vapors or mists. Use only in well-ventilated areas. Contaminated work clothing should not be allowed out of the workplace. Avoid prolonged or repeated contact with skin. Do not get in eyes. Do not puncture or incinerate cans.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Store away from incompatible materials. Do not store above the following temperature: 35°C (95°F).

Incompatible Materials

Strong oxidizers. Alkalis or alkaline earth metals powdered Al, Zn, Be, etc.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2-trans-Dichloroethylene 156-60-5	TWA: 200 ppm	-	-
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 1000 ppm; 2400 mg/m3	TWA: 250 ppm; 590 mg/m3

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Use splash goggles or face shield when contact may occur.

Skin and Body Protection

For prolonged or repeated skin contact use suitable protective gloves. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Respiratory Protection

Use supplied-air respiratory protection in confined or enclosed spaces.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Sweet
Appearance	Milky White Liquid	Odor Threshold	Not determined
Color	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	44.6 °C / 112 °F	
Flash Point	None	
Evaporation Rate	< 1	(Water = 1)
Flammability (Solid, Gas)	None	
Upper Flammability Limits	None	
Lower Flammability Limit	None	
Vapor Pressure	517 mm Hg	@ 20°C (68°F)
Vapor Density	4.0	(Air=1)
Specific Gravity	1.40	@ 20°C (68°F)
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

Strong oxidizers. Alkalis or alkaline earth metals powdered Al, Zn, Be, etc.

Hazardous Decomposition Products

Decomposition of this product at temperature above 300° C can form Hydrogen Fluoride (HF), but HF will only accumulate with continuous exposure to excess heat in a sealed vessel.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Eye Contact Avoid contact with eyes.

Skin Contact May be harmful in contact with skin. May cause an allergic skin reaction. Causes mild skin irritation.

Inhalation Harmful if inhaled.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
1,2-trans-Dichloroethylene 156-60-5	= 1235 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
Methyl Nonafluoro-isobutyl Ether 163702-08-7	> 5 g/kg (Rat)		= 100,000 ppm (Rat) 4 h
Methyl Nonafluoro-butyl Ether 163702-07-6	> 5 g/kg (Rat)		= 100,000 ppm (Rat) 4 h
Acetone 67-64-1	1800 mg/kg	20000 mg/kg	=76 mg/L/4H

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Not classifiable as a human carcinogen.

Legend

*IARC (International Agency for Research on Cancer)
Group 3 IARC components are "not classifiable as human carcinogens"*

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
1,2-trans-Dichloroethylene 156-60-5		135: 96 h Lepomis macrochirus mg/L LC50 static	EC50 = 1142 mg/L 5 min EC50 = 1546 mg/L 30 min	
1,1,1,2-Tetrafluoroethane 811-97-2		96 hour LC50-Rainbow Trout: 450 mg/L		48 hour EC50-Daphnia magna: 980 mg/L
Acetone 67-64-1		96 hour LC50-Rainbow Trout: 5540 mg/L		

Persistence/Degradability Not determined.

Bioaccumulation Not determined.

Mobility

Chemical Name	Partition Coefficient
1,2-trans-Dichloroethylene 156-60-5	1.48

Other Adverse Effects Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
1,2-trans-Dichloroethylene 156-60-5	U079	Included in waste streams: F024, F025, F039, K073		U079
Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
1,2-trans-Dichloroethylene 156-60-5	Category I - Volatiles		Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
1,2-trans-Dichloroethylene 156-60-5	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

SARA 313

Chemical Name	SARA/CERCLA RQ (lb)	SARA EHS TPQ (lb)
Acetone 67-64-1	5000	none

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
1,2-trans-Dichloroethylene 156-60-5 (<35)			X	
Acetone 67-64-1				

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	NJ	MA	PA	RI	MN	CA
1,2-trans-Dichloroethylene 156-60-5		X	X			
Acetone 76-64-1	X	X	X	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	0	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	0	0	B

Issue Date: 21-Dec-2004
Revision Date: 21-Apr-2022
Revision Note: 3-Year Update

Disclaimer

Information in the SDS is provided in good faith, but we assume no liability for its use or misuse. It is furnished without any warranty of merchantability or any other warranty, express or implied. We shall not be liable for any claims, losses or damages of any vendee or third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however they arise. Users must make their own investigations to determine suitability.

End of Safety Data Sheet